



221 Remington Fireball

.224"	22 Spitzer SP	22 TNT® HP
Weight (grains)	50	50
Ballistic Coefficient	0.207	0.228
Sectional Density	0.142	0.142
COAL Tested	1.830"	1.830"
Speer Part No.	1029	1030

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant 2400	Remington	CCI 400	13.5	2521	14.5	2693
IMR 4198	Remington	CCI 400	16.5	2503	17.5 C	2664
Alliant Reloder 7	Remington	CCI 400	16.9	2497	17.9	2638
IMR 4227	Remington	CCI 400	14.9	2490	15.9	2634
Hodgdon H110	Remington	CCI 450	12.5	2429	13.5	2625

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load