



30-30 Winchester (Handgun)

.308"	30 TNT® HP	30 HP	30 SPFN Hot- Cor®
Weight (grains)	125	130	130
Ballistic Coefficient	0.341	0.244	0.213
Sectional Density	0.188	0.196	0.196
COAL Tested	2.740"	2.730"	2.550"
Speer Part No.	1986	2005	2007

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 7	Winchester	CCI 200	27.0	2095	31.0	2328
Accurate 2460	Winchester	CCI 250	30.0	2037	34.0	2313
Accurate 2520	Winchester	CCI 250	31.0	2060	35.0	2296
Hodgdon H322	Winchester	CCI 200	29.0	1908	33.0	2260
Alliant Reloder 10X	Winchester	CCI 200	26.5	1938	30.5	2131
Hodgdon Varget	Winchester	CCI 200	31.0	1871	35.0	2106
Vihtavuori N140	Winchester	CCI 200	31.0	1868	35.0	2101
Winchester 748	Winchester	CCI 250	31.5	1889	35.5	2096
IMR 4895	Winchester	CCI 200	28.0	1686	32.0	1975
IMR 4064	Winchester	CCI 200	29.0	1634	33.0	1937

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load