



38 Special

.358"	38 LSWC	38 LSWC HP	38 LRN
Weight (grains)	158	158	158
Ballistic Coefficient	0.123	0.121	0.170
Sectional Density	0.176	0.176	0.176
COAL Tested	1.440"	1.455"	1.510"
Speer Part No.	4624	4628	4648

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
IMR SR 4756	Speer	CCI 500	5.0	844	5.6	967
Alliant Power Pistol	Speer	CCI 500	4.8	856	5.4	948
Accurate No. 5	Speer	CCI 500	5.8	874	6.2	922
Hodgdon H. Universal	Speer	CCI 500	4.2	827	4.6	902
Hodgdon Hi-Skor 700-X	Speer	CCI 500	3.2	774	3.8	877
Winchester 231	Speer	CCI 500	3.8	783	4.3	863
IMR PB	Speer	CCI 500	3.7	770	4.2	858
Hodgdon HP-38	Speer	CCI 500	3.6	756	4.1	855
Winchester WSF	Speer	CCI 500	3.8	738	4.3	830
Vihtavuori N350	Speer	CCI 500	4.5	717	5.0	818
Alliant Unique	Speer	CCI 500	4.0	740	4.7	815
Alliant Bullseye	Speer	CCI 500	3.1	752	3.5	814
Alliant Red Dot	Speer	CCI 500	3.0	727	3.4	793
Accurate No. 2	Speer	CCI 500	3.6	708	4.0	781

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load