



## 45 Automatic

|                              |             |
|------------------------------|-------------|
| <b>.452"</b>                 | <b>45</b>   |
| <b>Weight (grains)</b>       | <b>LSWC</b> |
| <b>Ballistic Coefficient</b> | 200         |
| <b>Sectional Density</b>     | 0.078       |
| <b>COAL Tested</b>           | 0.140       |
| <b>Speer Part No.</b>        | 1.190"      |
|                              | 4678        |

NOTE: These loads are not necessarily at maximum pressure. They are held to velocities popular for target shooting.

| Propellant            | Case  | Primer  | START CHARGE    |                            | MAXIMUM CHARGE  |                            |
|-----------------------|-------|---------|-----------------|----------------------------|-----------------|----------------------------|
|                       |       |         | Weight (grains) | Muzzle Velocity (feet/sec) | Weight (grains) | Muzzle Velocity (feet/sec) |
| Alliant Red Dot       | Speer | CCI 300 | 4.1             | 749                        | 4.5             | 831                        |
| Alliant Herco         | Speer | CCI 300 | 5.5             | 750                        | 6.0             | 826                        |
| IMR SR 7625           | Speer | CCI 300 | 4.7             | 726                        | 5.2             | 811                        |
| Alliant Bullseye      | Speer | CCI 300 | 4.2             | 744                        | 4.6             | 807                        |
| Hodgdon H. Universal  | Speer | CCI 300 | 4.9             | 710                        | 5.4             | 804                        |
| Winchester 231        | Speer | CCI 300 | 4.6             | 739                        | 5.0             | 803                        |
| IMR SR 4756           | Speer | CCI 300 | 5.3             | 728                        | 5.8             | 800                        |
| Alliant Unique        | Speer | CCI 300 | 4.9             | 716                        | 5.4             | 790                        |
| Hodgdon Hi-Skor 700-X | Speer | CCI 300 | 3.8             | 715                        | 4.2             | 790                        |

\* Data was shot in a 4.4" barrel.

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*