



45 Colt

.452"	45
Weight (grains)	GDHP
Ballistic Coefficient	250
Sectional Density	0.165
COAL Tested	0.175
COAL Tested	1.600"
Speer Part No.	4484

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Accurate No. 9	Winchester	CCI 350	DNR	—	14.0	874
Alliant Power Pistol	Winchester	CCI 300	DNR	—	8.8	845
Vihavuori N110	Winchester	CCI 300	DNR	—	16.0	843
Alliant Unique	Winchester	CCI 300	DNR	—	7.8	840
Accurate No. 5	Winchester	CCI 300	DNR	—	10.0	835
Alliant 2400	Winchester	CCI 300	DNR	—	15.0	826

DNR — do not reduce

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load