



480 Ruger

.475"	475
Weight (grains)	275
Ballistic Coefficient	0.162
Sectional Density	0.174
COAL Tested	1.640"
Speer Part No.	3973

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Winchester 296	Hornady	CCI 350	32.0	1590	34.0	1695
Hodgdon H110	Hornady	CCI 350	32.0	1554	34.0	1663
Vihtavuori N110	Hornady	CCI 300	25.5	1461	27.5	1575
Accurate No. 9	Hornady	CCI 300	26.0	1474	28.0	1566
Alliant 2400	Hornady	CCI 300	27.0	1454	29.0	1560
IMR 4227	Hornady	CCI 300	31.0	1424	33.0	1523
Accurate No. 7	Hornady	CCI 300	20.0	1314	22.0	1493
Alliant Power Pistol	Hornady	CCI 300	15.5	1324	17.5	1465
Alliant Unique	Hornady	CCI 300	14.0	1275	16.0	1400
Vihtavuori N350	Hornady	CCI 300	14.0	1205	16.0	1341

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load