



7mm T/CU

<b>.284"</b>	<b>7mm</b>
	<b>TNT® HP</b>
<b>Weight (grains)</b>	110
<b>Ballistic Coefficient</b>	0.384
<b>Sectional Density</b>	0.195
<b>COAL Tested</b>	2.410"
<b>Speer Part No.</b>	1616

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon H322	Federal	CCI 400	27.0	2184	<b>29.0</b>	2346
Accurate 2015	Federal	CCI 400	26.5	2175	<b>28.5</b>	2339
Vihtavuori N130	Federal	CCI 400	24.5	2133	<b>26.5</b>	2307
IMR 4895	Federal	CCI 400	28.3	2130	<b>30.3 C</b>	2281
Hodgdon BL-C(2)	Federal	CCI 400	31.0	2139	<b>33.0</b>	2277
Accurate 2230	Federal	CCI 400	27.5	2102	<b>29.5</b>	2255
Hodgdon H335	Federal	CCI 400	30.5	2115	<b>32.5</b>	2254
IMR 4198	Federal	CCI 400	21.5	1993	<b>23.5</b>	2178
IMR 3031	Federal	CCI 400	26.2	1997	<b>28.2 C</b>	2149
Hodgdon H4198	Federal	CCI 400	21.5	1928	<b>23.5</b>	2107
Winchester 748	Federal	CCI 400	30.5	1971	<b>32.5 C</b>	2100
Alliant Reloder 7	Federal	CCI 400	21.5	1887	<b>23.5</b>	2062

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*