



222 Remington

| | |
|------------------------------|-------------------|
| .224" | 22 |
| Weight (grains) | Spitzer SP |
| Ballistic Coefficient | 45 |
| Sectional Density | 0.143 |
| COAL Tested | 0.128 |
| Speer Part No. | 2.060" |
| | 1023 |

| Propellant | Case | Primer | START CHARGE | | MAXIMUM CHARGE | |
|---------------------------|-----------|-------------|-----------------|----------------------------|-----------------|----------------------------|
| | | | Weight (grains) | Muzzle Velocity (feet/sec) | Weight (grains) | Muzzle Velocity (feet/sec) |
| Hodgdon BL-C(2) | Remington | CCI 450 | 24.5 | 3148 | 26.5 C | 3498 |
| Accurate 2460 | Remington | CCI 450 | 23.0 | 3071 | 25.0 C | 3431 |
| Alliant Reloder 7 | Remington | CCI 400 | 19.5 | 3150 | 21.5 | 3424 |
| Accurate 2015 | Remington | CCI 400 | 21.0 | 3160 | 23.0 | 3398 |
| Alliant Power Pro Varmint | Federal | Federal 205 | 23.8 | 3056 | 26.3 | 3376 |
| Alliant Power Pro 1200-R | Federal | Federal 205 | 20.6 | 3040 | 22.9 | 3356 |
| Hodgdon H322 | Remington | CCI 400 | 21.5 | 3154 | 23.5 | 3338 |
| Accurate LT-30 | Federal | Federal 205 | 19.7 | 3009 | 21.9 | 3327 |
| Alliant Reloder 10X | Federal | Federal 205 | 21.0 | 3049 | 23.1 | 3307 |
| Accurate 2520 | Remington | CCI 450 | 24.0 | 3037 | 26.0 C | 3301 |
| IMR 4198 | Remington | CCI 400 | 18.5 | 3032 | 20.5 | 3278 |
| Hodgdon H4198 | Remington | CCI 400 | 18.5 | 3038 | 20.5 | 3267 |
| IMR 4895 | Remington | CCI 400 | 22.5 | 3064 | 24.5 C | 3260 |
| Winchester 748 | Remington | CCI 450 | 23.0 | 3008 | 25.0 | 3234 |
| Vihtavuori N120 | Remington | CCI 400 | 17.5 | 2910 | 19.5 | 3216 |
| Hodgdon H4895 | Remington | CCI 400 | 22.0 | 2942 | 24.0 C | 3215 |
| Hodgdon H335 | Remington | CCI 450 | 22.5 | 3002 | 24.5 | 3211 |
| Accurate 2230 | Remington | CCI 450 | 21.0 | 2891 | 23.0 | 3177 |

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load