



222 Remington

.224"	22 Spitzer SP	22 TNT® HP
Weight (grains)	50	50
Ballistic Coefficient	0.207	0.228
Sectional Density	0.142	0.142
COAL Tested	2.110"	2.130"
Speer Part No.	1029	1030

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Accurate 2015	Remington	CCI 400	21.0	3161	23.0	3345
Accurate 2520	Remington	CCI 450	24.0	3130	26.0 C	3270
Hodgdon BL-C(2)	Remington	CCI 450	24.0	2992	26.0	3238
Alliant Reloder 7	Remington	CCI 400	19.0	3010	21.0	3237
Hodgdon H322	Remington	CCI 400	21.0	2967	23.0	3225
Accurate 2460	Remington	CCI 450	22.0	2892	24.0	3224
IMR 3031	Remington	CCI 400	21.0	2959	23.0 C	3199
Accurate 2230	Remington	CCI 450	21.5	2890	23.5	3178
IMR 4895	Remington	CCI 400	22.0	2874	24.0 C	3158
Hodgdon H4895	Remington	CCI 400	22.0	2825	24.0 C	3156
IMR 4198	Remington	CCI 400	18.0	2931	20.0	3135
IMR 4320	Remington	CCI 400	24.0	2945	26.0 C	3134
Vihtavuori N120	Remington	CCI 400	17.0	2808	19.0	3126
Hodgdon H4198	Remington	CCI 400	18.0	2922	20.0	3109
Hodgdon H335	Remington	CCI 450	22.0	2800	24.0	3094
Alliant AR-Comp	Federal	Federal 205	20.3	2896	22.2 C	3094
Alliant Power Pro Varmint	Federal	Federal 205	22.0	2915	23.8	3087
Alliant Power Pro 1200-R	Federal	Federal 205	19.1	2827	21.1	3078
Hodgdon CFE 223	Federal	Federal 205	22.4	2845	24.4	3038
Alliant Reloder 10X	Federal	Federal 205	18.5	2722	20.4	2980
Accurate LT-30	Federal	Federal 205	17.2	2698	19.0	2940

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load