



speer®
bullets

223 Remington

.224"	22 Spitzer SP	22 TNT® HP
Weight (grains)	50	50
Ballistic Coefficient	0.207	0.228
Sectional Density	0.142	0.142
COAL Tested	2.185"	2.235"
Speer Part No.	1029	1030

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant AR-Comp	Federal	Federal 205	25.1	3256	27.8 C	3523
IMR 8208 XBR	Federal	Federal 205	24.7	3142	27.3	3471
Alliant Power Pro Varmint	Federal	Federal 205	25.1	3167	27.7	3467
Winchester 748	IMI	CCI 450	26.5	3130	28.5 C	3458
Alliant Reloder 15	Federal	Federal 205	26.2	3117	29.0 C	3437
Vihtavouri N135	Federal	Federal 205	24.2	3209	26.1	3398
Alliant Power Pro 1200-R	Federal	Federal 205	21.9	3132	24.2	3390
Accurate 2520	IMI	CCI 450	26.0	3229	28.0 C	3385
Hodgdon Varget	IMI	CCI 400	25.5	3079	27.5 C	3372
IMR 4895	IMI	CCI 400	25.0	3073	27.0 C	3369
Hodgdon H322	IMI	CCI 400	24.0	3045	26.0	3356
IMR 3031	IMI	CCI 400	24.0	3012	26.0 C	3339
Alliant Reloder 10X	IMI	CCI 400	21.5	3041	23.5	3322
Accurate 2015	IMI	CCI 400	22.5	2993	24.5	3320
Hodgdon H335	IMI	CCI 450	25.0	3018	27.0	3316
Vihtavuori N133	IMI	CCI 400	22.0	2939	24.0	3290
Hodgdon H4895	IMI	CCI 400	23.5	2910	25.5 C	3255
Hodgdon BL-C(2)	IMI	CCI 450	25.5	3004	27.5	3252
Hodgdon H4198	IMI	CCI 400	20.0	2888	22.0	3229
Accurate 2230	IMI	CCI 400	23.0	2885	25.0	3187
Accurate 5744 (reduced load)	IMI	CCI 400	11.0	1912	12.0	2058

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load