



223 Remington

.224"	22 HP	22 Match BTHP
Weight (grains)	52	52
Ballistic Coefficient	0.168	0.230
Sectional Density	0.148	0.148
COAL Tested	2.200"	2.200"
Speer Part No.	1035	1036

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Winchester 748	IMI	CCI 450	26.0	3187	28.0 C	3510
Alliant AR-Comp	Federal	Federal 205	24.0	3179	26.3 C	3394
IMR 8208 XBR	Federal	Federal 205	23.5	3081	26.1	3353
Alliant Power Pro Varmint	Federal	Federal 205	24.0	3032	26.5	3344
Hodgdon Varget	IMI	CCI 400	25.0	3039	27.0	3331
Alliant Reloder 15	Federal	Federal 205	24.9	3032	27.6 C	3322
Vihtavouri N135	Federal	Federal 205	22.8	3054	24.9 C	3277
Alliant Power Pro 1200-R	Federal	Federal 205	21.0	3020	23.1	3267
IMR 4895	IMI	CCI 400	24.5	2888	26.5 C	3254
IMR 3031	IMI	CCI 400	24.0	2915	26.0 C	3247
Alliant Reloder 10X	IMI	CCI 400	20.5	2955	22.5	3230
Vihtavuori N133	IMI	CCI 400	22.0	2864	24.0	3226
Hodgdon H4895	IMI	CCI 400	23.5	2902	25.5 C	3196
Hodgdon H335	IMI	CCI 450	24.5	2919	26.5	3178
Hodgdon H322	IMI	CCI 400	22.5	2859	24.5	3149
IMR 4064	IMI	CCI 400	24.0	2878	26.0 C	3134
Hodgdon BL-C(2)	IMI	CCI 450	25.0	2728	27.0	3108
Accurate 2460	IMI	CCI 450	23.0	2785	25.0	3102
Alliant Reloder 7	IMI	CCI 400	18.5	2639	20.5	2972
Accurate 5744 (reduced load)	IMI	CCI 400	11.0	1906	12.0	2047

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load