



speer
bullets

223 Remington

0.224	22
	Semi-Spitzer SP
Weight (grains)	70
Ballistic Coefficient	0.219
Sectional Density	0.199
COAL Tested	2.140"
Speer Part No.	1053

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Winchester 748	IMI	CCI 450	25.0	2862	27.0	3115
Alliant Power Pro 2000-MR	Federal	Federal 205	25.0	2775	27.1	2982
Hodgdon H414	IMI	CCI 450	26.0	2690	28.0	2923
Hodgdon Varget	Federal	Federal 205	22.4	2659	24.8 C	2901
Alliant Power Pro Varmint	Federal	Federal 205	21.0	2632	23.2	2872
Alliant Reloder 15	Federal	Federal 205	22.5	2708	24.1 C	2871
IMR 4895	IMI	CCI 400	22.5	2658	24.5 C	2864
Hodgdon H335	IMI	CCI 450	22.5	2621	24.5	2849
Alliant AR-Comp	Federal	Federal 205	20.0	2679	21.9	2834
Accurate 2460	IMI	CCI 450	21.5	2526	23.5	2814
Accurate 2230	IMI	CCI 400	21.0	2489	23.0	2749
Hodgdon H380	IMI	CCI 450	26.0	2560	28.0	2733
Vihtavuori N135	IMI	CCI 400	20.5	2449	22.5	2693
IMR 4320	IMI	CCI 400	22.5	2474	24.5	2675
Hodgdon BL-C(2)	IMI	CCI 450	21.5	2474	23.5	2648
Accurate 2015	IMI	CCI 400	18.0	2348	20.0	2583

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load