



223 Remington

.224"	22 TNT Green®
Weight (grains)	50
Ballistic Coefficient	0.190
Sectional Density	0.142
COAL Tested	2.150"
Speer Part No.	1028

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon Varget	Federal	Federal 205	24.5	3115	26.5 C	3322
Winchester 748	Federal	Federal 205	24.0	3114	26.0 C	3308
Ranshot TAC	Federal	Federal 205	23.0	3070	25.0	3295
Alliant Reloder 10X	Federal	Federal 205	20.0	3002	22.0	3245
Vihtavuori N540	Federal	Federal 205	23.5	2970	25.5	3218
IMR 4895	Federal	Federal 205	23.5	2908	25.5 C	3169

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load