



225 Winchester

.224"	22
Weight (grains)	Spitzer SP
Ballistic Coefficient	45
Sectional Density	0.143
COAL Tested	0.128
Speer Part No.	2.240"
	1023

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
IMR 4064	Winchester	CCI 200	30.0	3284	34.0	3737
Winchester 748	Winchester	CCI 250	31.0	3237	35.0	3666
IMR 3031	Winchester	CCI 200	28.0	3176	32.0	3650
Winchester 760	Winchester	CCI 250	34.0	3244	38.0 C	3639
Hodgdon H322	Winchester	CCI 200	27.0	3163	31.0	3609
Hodgdon H380	Winchester	CCI 250	34.0	3181	38.0 C	3588
IMR 4350	Winchester	CCI 200	33.0	3164	37.0 C	3535
Hodgdon H335	Winchester	CCI 250	27.0	3011	31.0	3452
IMR SR 4759 (reduced load)	Winchester	CCI 200	9.0	1659	11.0	2039

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load