



## 240 Weatherby Magnum

<b>.243"</b>	<b>6mm</b>
<b>Weight (grains)</b>	<b>HP</b>
<b>Ballistic Coefficient</b>	75
<b>Sectional Density</b>	0.192
<b>COAL Tested</b>	0.181
<b>Speer Part No.</b>	3.060"
	1205

NOTE: 6mm TNT not recommended for this cartridge.

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon H414	Weatherby	CCI 250	52.0	3447	<b>56.0</b>	3734
IMR 4831	Weatherby	CCI 250	51.0	3322	<b>55.0 C</b>	3620
Winchester 760	Weatherby	CCI 250	47.5	3281	<b>51.5</b>	3602
IMR 4350	Weatherby	CCI 250	49.0	3334	<b>53.0</b>	3583
IMR 4064	Weatherby	CCI 250	42.0	3126	<b>46.0</b>	3481
Hodgdon H380	Weatherby	CCI 250	45.0	3094	<b>49.0</b>	3429

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*