



## 240 Weatherby Magnum

<b>.243"</b>	<b>6mm</b>
<b>Weight (grains)</b>	<b>Spitzer SP Hot-Cor®</b>
<b>Ballistic Coefficient</b>	90
<b>Sectional Density</b>	0.365
<b>COAL Tested</b>	0.218
<b>Speer Part No.</b>	3.060"
	1217

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
IMR 4831	Weatherby	CCI 250	48.0	3176	<b>52.0 C</b>	3420
Hodgdon H414	Weatherby	CCI 250	48.0	3057	<b>52.0</b>	3367
IMR 4350	Weatherby	CCI 250	46.5	3059	<b>50.5</b>	3304
Winchester 760	Weatherby	CCI 250	46.0	2992	<b>50.0</b>	3302
Hodgdon H380	Weatherby	CCI 250	43.0	2813	<b>47.0</b>	3107
IMR 4064	Weatherby	CCI 250	40.0	2854	<b>44.0</b>	3098

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*