



260 Remington

| | |
|------------------------------|----------------|
| .264" | 6.5mm |
| | TNT® HP |
| Weight (grains) | 90 |
| Ballistic Coefficient | 0.281 |
| Sectional Density | 0.184 |
| COAL Tested | 2.650" |
| Speer Part No. | 1445 |

| Propellant | Case | Primer | START CHARGE | | MAXIMUM CHARGE | |
|------------------------------|-----------|-------------|-----------------|----------------------------|-----------------|----------------------------|
| | | | Weight (grains) | Muzzle Velocity (feet/sec) | Weight (grains) | Muzzle Velocity (feet/sec) |
| Alliant Reloader 16 | Federal | Federal 210 | 43.7 | 3086 | 48.4 C | 3392 |
| Hodgdon H380 | Remington | CCI 250 | 45.0 | 3125 | 49.0 | 3367 |
| Alliant AR-Comp | Federal | Federal 210 | 37.1 | 3127 | 41.1 | 3365 |
| Hodgdon H414 | Remington | CCI 250 | 46.0 | 3046 | 50.0 | 3348 |
| Hodgdon CFE 223 | Federal | Federal 210 | 37.8 | 3051 | 42.0 | 3328 |
| Vihtavuori N160 | Remington | CCI 200 | 47.0 | 3008 | 51.0 C | 3315 |
| Alliant Reloder 15 | Remington | CCI 200 | 41.5 | 2970 | 45.5 | 3311 |
| IMR 8208 XBR | Federal | Federal 210 | 36.3 | 3152 | 39.4 | 3309 |
| IMR 4064 | Remington | CCI 200 | 40.0 | 2910 | 44.0 | 3297 |
| IMR 4350 | Remington | CCI 200 | 46.0 | 2947 | 50.0 C | 3268 |
| Hodgdon Varget | Remington | CCI 200 | 40.5 | 2959 | 44.5 | 3261 |
| Winchester 760 | Remington | CCI 250 | 46.5 | 3096 | 48.5 | 3253 |
| Winchester 748 | Remington | CCI 250 | 40.0 | 2904 | 44.0 | 3250 |
| Accurate 2700 | Remington | CCI 250 | 46.0 | 3071 | 48.0 | 3247 |
| IMR 4895 | Remington | CCI 200 | 39.0 | 2841 | 43.0 | 3205 |
| Accurate 4350 | Remington | CCI 200 | 46.0 | 2852 | 48.0 C | 3000 |
| Alliant Reloder 19 | Remington | CCI 200 | 48.0 | 2855 | 50.0 C | 2985 |
| Accurate 5744 (reduced load) | Remington | CCI 200 | 20.0 | 1981 | 24.0 | 2294 |

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load