



## 280 Remington (7mm Remington Express)

.284"	7mm Spitzer SP Hot-Cor®	7mm Spitzer BTSP
Weight (grains)	130	130
Ballistic Coefficient	0.368	0.424
Sectional Density	0.230	0.230
COAL Tested	3.205"	3.205"
Speer Part No.	1623	1624

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 16	Federal	Federal 210	51.3	2896	<b>56.8</b>	3139
Alliant Reloder 19	Remington	CCI 200	55.0	2835	<b>59.0</b>	3134
Alliant Power Pro 4000-MR	Federal	Federal 210	54.0	2937	<b>57.8</b>	3114
IMR 4831	Remington	CCI 200	53.0	2828	<b>57.0</b>	3108
IMR 4350	Remington	CCI 200	53.0	2773	<b>57.0</b>	3106
Alliant Reloder 17	Federal	Federal 210	50.4	2845	<b>55.7</b>	3102
Hodgdon H4350	Remington	CCI 200	50.0	2827	<b>54.0</b>	3073
Accurate 4350	Remington	CCI 200	53.0	2791	<b>57.0</b>	3066
Ramshot Big Game	Federal	Federal 210	47.2	2790	<b>52.1</b>	3014
Hodgdon H414	Remington	CCI 250	48.5	2844	<b>52.5</b>	2993
Hodgdon H4831SC	Remington	CCI 200	53.5	2783	<b>57.5</b>	2993
Alliant Power Pro 2000-MR	Federal	Federal 210	46.4	2783	<b>50.6</b>	2993
Vihavuori N160	Remington	CCI 200	50.0	2794	<b>54.0</b>	2977
Winchester 760	Remington	CCI 250	48.5	2801	<b>52.5</b>	2975
Accurate 3100	Remington	CCI 200	54.0	2721	<b>58.0</b>	2972
IMR 4895	Remington	CCI 200	42.0	2790	<b>46.0</b>	2969
Alliant Reloder 15	Remington	CCI 200	43.0	2774	<b>47.0</b>	2967
IMR 4064	Remington	CCI 200	43.0	2729	<b>47.0</b>	2958
IMR 4320	Remington	CCI 200	43.0	2743	<b>47.0</b>	2946
IMR SR 4759 (reduced load)	Remington	CCI 200	20.0	1680	<b>24.0</b>	2024

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*