



284 Winchester

.284"	7mm
	TNT® HP
Weight (grains)	110
Ballistic Coefficient	0.384
Sectional Density	0.195
COAL Tested	2.780"
Speer Part No.	1616

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Winchester 760	Winchester	CCI 250	58.0	3259	62.0 C	3499
Alliant Reloder 15	Winchester	CCI 200	53.0	3185	57.0	3443
Accurate 2460	Winchester	CCI 250	48.0	3122	52.0	3412
Winchester 748	Winchester	CCI 250	53.0	3134	57.0	3410
Hodgdon BL-C(2)	Winchester	CCI 250	52.0	3121	56.0	3403
Hodgdon H414	Winchester	CCI 250	57.0	3155	61.0 C	3398
Vihtavuori N135	Winchester	CCI 200	48.0	3047	52.0	3337
IMR 4350	Winchester	CCI 200	56.0	3045	60.0 C	3273
IMR 4831	Winchester	CCI 200	58.0	3016	62.0 C	3252
Alliant Reloder 19	Winchester	CCI 200	58.0	2976	62.0 C	3209
Hodgdon H4350	Winchester	CCI 200	55.0	2919	59.0 C	3138
Accurate 4350	Winchester	CCI 200	55.0	2899	59.0 C	3116

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load