



## 30-06 Springfield

.308"	30 Spitzer BTSP	30 Spitzer SP Hot Cor®	30 Grand Slam® SP/CANN
Weight (grains)	180	180	180
Ballistic Coefficient	0.545	0.441	0.374
Sectional Density	0.271	0.271	0.271
COAL Tested	3.250"	3.160"	3.160"
Speer Part No.	2052	2053	2063

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Ramshot Hunter	Federal	Federal 210	54.1	2592	<b>59.2 C</b>	2797
Hodgdon H4350	Winchester	CCI 200	54.0	2671	<b>58.0 C</b>	2791
IMR 4064	Winchester	CCI 200	46.0	2612	<b>50.0</b>	2791
Alliant Reloder 16	Federal	Federal 210	49.8	2545	<b>55.2 C</b>	2770
Alliant Reloder 23	Federal	Federal 210	53.2	2503	<b>59.9 C</b>	2769
Alliant Power Pro 4000-MR	Federal	Federal 210	51.4	2552	<b>57.1 C</b>	2764
Alliant Reloder 22	Winchester	CCI 200	58.0	2648	<b>62.0 C</b>	2755
Hodgdon H4831SC	Winchester	CCI 200	60.0	2610	<b>62.0 C</b>	2753
Alliant Reloder 17	Federal	Federal 210	49.0	2522	<b>54.4</b>	2732
IMR 4831	Winchester	CCI 200	55.0	2572	<b>59.0 C</b>	2716
Winchester 760	Winchester	CCI 250	51.0	2567	<b>55.0</b>	2709
Hodgdon H414	Winchester	CCI 250	51.0	2573	<b>55.0</b>	2705
Alliant Reloder 19	Winchester	CCI 200	55.0	2483	<b>59.0 C</b>	2671
IMR 4350	Winchester	CCI 200	52.0	2523	<b>56.0 C</b>	2670
Alliant Power Pro 2000-MR	Federal	Federal 210	45.0	2445	<b>49.8</b>	2666
Accurate 4350	Winchester	CCI 200	53.0	2469	<b>57.0 C</b>	2645
Vihtavuori N160	Winchester	CCI 200	52.0	2351	<b>56.0</b>	2584
Alliant Reloder 15	Winchester	CCI 200	45.0	2434	<b>49.0</b>	2579
IMR 4895	Winchester	CCI 200	43.0	2387	<b>47.0</b>	2564
IMR 4198 (reduced load)	Winchester	CCI 200	26.0	1725	<b>30.0</b>	2010

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*