



30-40 Krag

<b>.308"</b>	<b>30</b>
<b>Weight (grains)</b>	<b>Plinker® SPRN</b>
<b>Ballistic Coefficient</b>	100
<b>Sectional Density</b>	0.144
<b>COAL Tested</b>	0.151
<b>Speer Part No.</b>	2.610"
	1805

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
<b>Hodgdon H322</b>	Winchester	CCI 200	41.0	2795	<b>45.0</b>	3140
<b>IMR 4320</b>	Winchester	CCI 200	44.0	2765	<b>48.0</b>	3015
<b>IMR 3031</b>	Winchester	CCI 200	40.0	2604	<b>44.0</b>	2886
<b>Hodgdon H380</b>	Winchester	CCI 250	47.0	2653	<b>51.0</b>	2876
<b>IMR 4064</b>	Winchester	CCI 200	42.0	2593	<b>46.0</b>	2867
<b>IMR 4895</b>	Winchester	CCI 200	40.0	2511	<b>44.0</b>	2783
<b>IMR 4350</b>	Winchester	CCI 200	49.0	2465	<b>53.0</b>	2680
<b>IMR SR 4759 (reduced load)</b>	Winchester	CCI 200	16.0	1568	<b>20.0</b>	1953

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*