



30-40 Krag

.308"	30 SPFN Hot-Cor®	30 Spitzer BTSP	30 Spitzer SP Hot-Cor®	30 Grand Slam® SP/CANN
Weight (grains)	150	150	150	150
Ballistic Coefficient	0.255	0.417	0.377	0.295
Sectional Density	0.226	0.226	0.226	0.226
COAL Tested	3.089"	3.089"	3.089"	3.089"
Speer Part No.	2011	2022	2023	2026

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
IMR 4350	Winchester	CCI 200	46.0	2236	50.0	2494
IMR 3031	Winchester	CCI 200	37.0	2235	41.0	2491
IMR 4064	Winchester	CCI 200	38.0	2229	42.0	2489
Hodgdon H380	Winchester	CCI 250	43.0	2220	47.0	2480
Hodgdon H414	Winchester	CCI 250	45.0	2169	49.0	2416
IMR 4895	Winchester	CCI 200	35.0	2063	39.0	2356
Hodgdon H322	Winchester	CCI 200	31.0	1886	35.0	2173
IMR SR 4759 (reduced load)	Winchester	CCI 200	21.0	1631	25.0	1937

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load