



30-40 Krag

.308"	30 Spitzer BTSP	30 Spitzer SP Hot-Cor®	30 Grand Slam® SP/CANN
Weight (grains)	180	180	180
Ballistic Coefficient	0.545	0.441	0.374
Sectional Density	0.271	0.271	0.271
COAL Tested	3.089"	3.089"	3.089"
Speer Part No.	2052	2053	2063

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
IMR 4831	Winchester	CCI 200	43.0	1997	47.0	2185
IMR 4350	Winchester	CCI 200	42.0	1960	46.0	2146
IMR 4895	Winchester	CCI 200	33.0	1841	37.0	2146
Winchester 760	Winchester	CCI 250	41.0	1914	45.0	2143
IMR 3031	Winchester	CCI 200	33.0	1876	37.0	2139
IMR 4064	Winchester	CCI 200	34.0	1872	38.0	2132
Hodgdon H414	Winchester	CCI 250	39.0	1855	43.0	2051
IMR 4198 (reduced load)	Winchester	CCI 200	24.0	1589	28.0	1863

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load