



300 Savage

.308"	30 Varminter HP	30 Carbine TMJ® RN
Weight (grains)	110	110
Ballistic Coefficient	0.128	0.179
Sectional Density	0.166	0.166
COAL Tested	2.255"	2.330"
Speer Part No.	1835	1846

Note: Limit 110 HP velocities to 2900 fps maximum

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Accurate 2230	Federal	CCI 250	41.0	2776	45.0	3096
Hodgdon H322	Federal	CCI 200	40.0	2899	44.0	3070
Vihtavuori N130	Federal	CCI 200	36.0	2738	40.0	3032
Winchester 748	Federal	CCI 250	43.0	2749	47.0 C	3025
IMR 3031	Federal	CCI 200	38.0	2671	42.0 C	2953
IMR 4064	Federal	CCI 200	41.0	2644	45.0 C	2926
IMR 4895	Federal	CCI 200	40.0	2641	44.0 C	2909
IMR 4198	Federal	CCI 200	31.0	2552	35.0	2895
Alliant Reloder 7	Federal	CCI 200	34.0	2549	38.0	2885
Hodgdon H380	Federal	CCI 250	44.0	2500	48.0 C	2750
IMR 4350	Federal	CCI 200	42.0	2309	46.0 C	2559
IMR SR 4759 (reduced load)	Federal	CCI 200	15.0	1525	19.0	1939

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load