



## 300 Savage

.308"	30 Spitzer BTSP	30 Spitzer SP Hot-Cor®	30 Grand Slam® SP/CANN
Weight (grains)	165	165	165
Ballistic Coefficient	0.520	0.444	0.354
Sectional Density	0.248	0.248	0.248
COAL Tested	2.550"	2.550"	2.540"
Speer Part No.	2034	2035	2038

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 15	Federal	CCI 200	40.0	2392	<b>44.0 C</b>	2674
Vihtavuori N140	Federal	CCI 200	39.0	2368	<b>43.0 C</b>	2647
Hodgdon H322	Federal	CCI 200	35.0	2238	<b>39.0</b>	2519
IMR 4064	Federal	CCI 200	36.0	2229	<b>40.0</b>	2493
Hodgdon H380	Federal	CCI 250	41.0	2254	<b>45.0 C</b>	2474
Winchester 748	Federal	CCI 250	37.0	2224	<b>41.0</b>	2468
IMR 4895	Federal	CCI 200	35.0	2169	<b>39.0</b>	2443
Accurate 2700	Federal	CCI 250	40.0	2207	<b>44.0 C</b>	2434
IMR 4350	Federal	CCI 200	41.0	2180	<b>45.0 C</b>	2425
IMR 4320	Federal	CCI 200	36.0	2120	<b>40.0</b>	2384
IMR SR 4759 (reduced load)	Federal	CCI 200	19.0	1594	<b>21.0</b>	1783

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load