



300 Winchester Magnum

.308"	30 Spitzer BTSP	30 Spitzer SP Hot-Cor®	30 Grand Slam® SP
Weight (grains)	180	180	180
Ballistic Coefficient	0.545	0.441	0.374
Sectional Density	0.271	0.271	0.271
COAL Tested	3.340"	3.340"	3.285"
Speer Part No.	2052	2053	2063

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 26	Federal	Federal 215	70.1	2763	77.8 C	3084
Alliant Reloder 19	Winchester	CCI 250	72.0	2845	76.0	3059
Alliant Reloder 22	Winchester	CCI 250	73.0	2844	77.0 C	3055
Alliant Reloder 25	Winchester	CCI 250	75.5	2893	79.5 C	3050
Alliant Reloder 23	Federal	Federal 215	69.8	2767	76.8 C	3041
Alliant Power Pro 4000-MR	Federal	Federal 215	66.9	2762	74.0	3033
Alliant Reloder 17	Federal	Federal 215	63.6	2780	70.5	3007
IMR 7828	Winchester	CCI 250	74.0	2818	78.0 C	2990
IMR 4350	Winchester	CCI 250	68.0	2802	72.0	2988
Alliant Reloder 16	Federal	Federal 215	63.4	2738	70.3	2987
IMR 4831	Winchester	CCI 250	69.0	2789	73.0 C	2951
Hodgdon H4831SC	Winchester	CCI 250	71.0	2816	75.0	2950
Hodgdon H1000	Winchester	CCI 250	77.0	2781	81.0 C	2943
Hodgdon H4350	Winchester	CCI 250	67.0	2762	71.0	2938
Accurate 3100	Winchester	CCI 250	71.0	2762	75.0 C	2937
Vihtavuori N160	Winchester	CCI 250	68.0	2754	72.0	2925
Winchester 760	Winchester	CCI 250	61.0	2670	65.0	2811
Hodgdon H414	Winchester	CCI 250	60.0	2647	64.0	2786
Accurate 8700	Winchester	CCI 250	82.0	2526	86.0 C	2716
IMR 4198 (reduced load)	Winchester	CCI 250	31.0	1879	33.0	1998

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load