



308 Norma Magnum

.308"	30
Weight (grains)	Plinker® SPRN
Ballistic Coefficient	100
Sectional Density	0.144
COAL Tested	0.151
Speer Part No.	2.870"
	1805

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon H414	Norma	CCI 250	73.0	3396	77.0	3645
Hodgdon H380	Norma	CCI 250	66.0	2383	70.0	3481
IMR 3031	Norma	CCI 250	57.0	3218	61.0	3433
IMR 4895	Norma	CCI 250	59.0	3196	63.0	3407
IMR 4064	Norma	CCI 250	62.0	3166	66.0	3373
IMR 4320	Norma	CCI 250	62.0	3146	66.0	3352
IMR 4198	Norma	CCI 250	46.0	2966	50.0	3207
IMR SR 4759 (reduced load)	Norma	CCI 250	20.0	1738	22.0	1906

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load