



308 Winchester

.308"	30 Carbine TMJ® RN
Weight (grains)	110
Ballistic Coefficient	0.179
Sectional Density	0.166
COAL Tested	2.490"
Speer Part No.	1846

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Accurate 2460	IMI Commercial	CCI 250	46.0	2870	50.0 C	3271
Hodgdon H322	IMI Commercial	CCI 200	42.0	2944	46.0	3206
Alliant Reloder 15	IMI Commercial	CCI 200	47.0	2868	51.0 C	3194
Accurate 2520	IMI Commercial	CCI 250	45.0	2899	49.0 C	3193
IMR 3031	IMI Commercial	CCI 200	44.0	2886	48.0 C	3179
IMR 4895	IMI Commercial	CCI 200	44.5	2848	48.5 C	3172
IMR 4320	IMI Commercial	CCI 200	47.0	2860	51.0 C	3115
Hodgdon Varget	IMI Commercial	CCI 200	46.0	2957	48.0 C	3108
Hodgdon H4895	IMI Commercial	CCI 200	43.0	2689	47.0 C	3064
Winchester 748	IMI Commercial	CCI 250	47.0	2682	51.0	3058
Vihtavuori N120	IMI Commercial	CCI 200	34.0	2708	38.0	3051
IMR 4064	IMI Commercial	CCI 200	44.5	2708	48.5 C	3051
IMR 4198 (reduced load)	IMI Commercial	CCI 200	26.0	1935	30.0	2286

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load