



## 308 Winchester

.308"	30 HP	30 SPFN Hot- Cor®
Weight (grains)	130	130
Ballistic Coefficient	0.244	0.213
Sectional Density	0.196	0.196
COAL Tested	2.615"	2.530"
Speer Part No.	2005	2007

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant AR-Comp	Federal	Federal 210	43.3	2908	<b>48.6 C</b>	3178
Alliant Reloder 10X	IMI Commercial	CCI 200	38.0	2845	<b>42.0</b>	3120
Alliant Reloder 15	IMI Commercial	CCI 200	46.0	2791	<b>50.0 C</b>	3108
Alliant Power Pro Varmint	Federal	Federal 210	42.9	2823	<b>47.7</b>	3108
Accurate 2460	IMI Commercial	CCI 250	44.0	2727	<b>48.0 C</b>	3107
IMR 4320	IMI Commercial	CCI 200	46.0	2695	<b>50.0 C</b>	3036
Accurate 2230	IMI Commercial	CCI 250	42.0	2654	<b>46.0 C</b>	3025
Winchester 748	IMI Commercial	CCI 250	46.0	2760	<b>50.0 C</b>	3006
Accurate 2520	IMI Commercial	CCI 250	44.0	2714	<b>48.0 C</b>	2989
Hodgdon H322	IMI Commercial	CCI 200	40.0	2669	<b>44.0</b>	2972
Vihtavuori N135	IMI Commercial	CCI 200	42.0	2661	<b>46.0 C</b>	2963
IMR 4895	IMI Commercial	CCI 200	42.0	2685	<b>46.0 C</b>	2957
Hodgdon Varget	IMI Commercial	CCI 200	45.0	2820	<b>47.0 C</b>	2954
IMR 4064	IMI Commercial	CCI 200	44.0	2643	<b>48.0 C</b>	2943
IMR 3031	IMI Commercial	CCI 200	41.0	2702	<b>48.0 C</b>	2942
IMR 4198 (reduced load)	IMI Commercial	CCI 200	25.0	1978	<b>29.0</b>	2201

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load