



308 Winchester

.308"	30 SPFN Hot-Cor®	30 Spitzer BTSP	30 Spitzer SP Hot-Cor®	30 Grand Slam® SP
Weight (grains)	150	150	150	150
Ballistic Coefficient	0.255	0.417	0.377	0.295
Sectional Density	0.226	0.266	0.266	0.266
COAL Tested	2.530"	2.700"	2.700"	2.680"
Speer Part No.	2011	2022	2023	2026

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pro 2000-MR	Federal	Federal 210	48.3	2823	52.8 C	3037
Alliant Reloder 15	IMI Commercial	CCI 200	45.0	2715	49.0 C	2960
Alliant Power Pro Varmint	Federal	Federal 210	42.3	2738	47.1	2959
Accurate 2520	IMI Commercial	CCI 250	44.0	2593	48.0 C	2956
Alliant AR-Comp	Federal	Federal 210	40.6	2718	45.2 C	2948
Hodgdon H335	IMI Commercial	CCI 250	43.0	2590	47.0	2919
Winchester 748	IMI Commercial	CCI 250	46.0	2684	50.0 C	2907
IMR 8208 XBR	Federal	Federal 210	39.5	2695	43.9	2907
Hodgdon Varget	IMI Commercial	CCI 200	43.0	2663	47.0 C	2895
Vihtavuori N140	Federal	Federal 210	41.9	2653	46.5 C	2892
Vihtavuori N135	IMI Commercial	CCI 200	42.0	2635	46.0 C	2859
IMR 4064	IMI Commercial	CCI 200	43.0	2560	47.0 C	2851
IMR 4320	IMI Commercial	CCI 200	44.0	2514	48.0 C	2831
IMR 4895	IMI Commercial	CCI 200	41.0	2582	45.0	2812
IMR 3031	IMI Commercial	CCI 200	40.0	2458	44.0	2797
Alliant Reloder 10X	IMI Commercial	CCI 200	35.5	2526	39.5	2790
Hodgdon H414	IMI Commercial	CCI 250	47.0	2345	51.0 C	2673
Hodgdon BL-C(2)	IMI Commercial	CCI 250	40.0	2394	44.0	2637
SR 4759 (reduced load)	IMI Commercial	CCI 200	21.0	1632	25.0	1933

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load