



## 308 Winchester

<b>.308"</b>	<b>30</b>
	<b>Spitzer SP Hot-</b>
	<b>Cor®</b>
<b>Weight (grains)</b>	200
<b>Ballistic Coefficient</b>	0.478
<b>Sectional Density</b>	0.301
<b>COAL Tested</b>	2.800"
<b>Speer Part No.</b>	2211

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
<b>Alliant Reloder 15</b>	IMI Commercial	CCI 200	38.0	2140	<b>42.0</b>	2439
<b>Winchester 748</b>	IMI Commercial	CCI 250	39.0	2240	<b>43.0</b>	2439
<b>Accurate 2460</b>	IMI Commercial	CCI 200	36.5	2215	<b>40.5</b>	2438
<b>Hodgdon H414</b>	IMI Commercial	CCI 250	42.0	2138	<b>46.0 C</b>	2437
<b>Winchester 760</b>	IMI Commercial	CCI 250	44.0	2215	<b>48.0 C</b>	2412
<b>IMR 4350</b>	IMI Commercial	CCI 200	43.0	2127	<b>47.0 C</b>	2396
<b>IMR 4320</b>	IMI Commercial	CCI 200	38.0	2171	<b>42.0</b>	2391
<b>IMR 4895</b>	IMI Commercial	CCI 200	36.0	2095	<b>40.0</b>	2388
<b>Hodgdon H380</b>	IMI Commercial	CCI 250	43.0	2141	<b>47.0 C</b>	2384
<b>IMR 4831</b>	IMI Commercial	CCI 200	43.0	2139	<b>47.0 C</b>	2382
<b>Vihtavuori N140</b>	IMI Commercial	CCI 200	37.0	2106	<b>41.0</b>	2373
<b>Accurate 2520</b>	IMI Commercial	CCI 250	36.0	2171	<b>40.0</b>	2365
<b>IMR 4064</b>	IMI Commercial	CCI 200	36.5	2060	<b>40.5</b>	2347
<b>IMR 4198 (reduced load)</b>	IMI Commercial	CCI 200	24.0	1510	<b>28.0</b>	1760

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*