



30 M1 Carbine

.308"	30
Weight (grains)	SPRN Plinker® 100
Ballistic Coefficient	0.144
Sectional Density	0.151
COAL Tested	1.625"
Speer Part No.	1805

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Accurate No. 9	IMI	CCI 400	12.3	1930	14.3	2232
Winchester 296	IMI	CCI 450	13.5	1765	15.5	2041
Hodgdon H110	IMI	CCI 450	12.5	1680	14.5	1977
IMR 4227	IMI	CCI 400	13.5	1697	15.5	1971
Vihtavuori N110	IMI	CCI 400	11.0	1700	13.0 C	1964
Alliant 2400	IMI	CCI 400	10.5	1516	12.5	1831
IMR 4198	IMI	CCI 400	13.5	1444	15.5	1688
Accurate 1680	IMI	CCI 400	14.0	1451	16.0 C	1679

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load