



338 Remington Ultra Magnum

0.338	338 Spitzer BTSP
Weight (grains)	225
Ballistic Coefficient	0.497
Sectional Density	0.281
COAL Tested	3.600"
Speer Part No.	2406

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 25	Federal	Federal 215	95.0	2965	99.0 C	3103
Ramshot Magnum	Federal	Federal 215	98.0	2953	102.0 C	3062
Vihtavuori N560	Federal	Federal 215	89.0	2911	93.0	3045
Alliant Reloder 22	Federal	Federal 215	89.0	2891	93.0	3029
Alliant Reloder 19	Federal	Federal 215	87.0	2884	91.0	3028
Hodgdon Retumbo	Federal	Federal 215	97.0	2913	101.0 C	3015
Accurate MagPro	Federal	Federal 215	92.0	2922	96.0	3007
IMR 7828	Federal	Federal 215	88.0	2840	92.0	2998
IMR 4831	Federal	Federal 215	83.0	2839	87.0	2997
Hodgdon H4831SC	Federal	Federal 215	88.0	2833	92.0	2965

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load