



## 358 Winchester

.358"	35
Weight (grains)	SPFN Hot-Cor® 180
Ballistic Coefficient	0.236
Sectional Density	0.201
COAL Tested	2.680"
Speer Part No.	2435

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon H335	Winchester	CCI 250	48.0	2537	52.0	2766
Alliant Reloder 7	Winchester	CCI 200	41.0	2481	45.0	2762
IMR 3031	Winchester	CCI 200	47.0	2506	51.0	2755
IMR 4895	Winchester	CCI 200	47.0	2492	51.0	2734
Hodgdon H322	Winchester	CCI 200	46.0	2492	50.0	2713
IMR 4198	Winchester	CCI 200	38.0	2401	42.0	2706
Vihtavuori N133	Winchester	CCI 200	44.0	2494	48.0 C	2700
Accurate 2015	Winchester	CCI 200	43.0	2424	47.0 C	2658
Hodgdon BL-C(2)	Winchester	CCI 250	49.0	2439	53.0 C	2619
Winchester 748	Winchester	CCI 250	49.0	2360	53.0	2593
IMR 4320	Winchester	CCI 200	47.0	2443	51.0	2593

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*