



## 375 Remington Ultra Magnum

<b>.375"</b>	<b>375</b>
<b>Weight (grains)</b>	<b>Spitzer BTSP</b>
<b>Ballistic Coefficient</b>	270
<b>Sectional Density</b>	0.478
<b>COAL Tested</b>	0.274
<b>Speer Part No.</b>	3.600"
	2472

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 19	Remington	CCI 250	93.4	2782	<b>103.7 C</b>	3078
Vihtavuori N560	Remington	CCI 250	93.7	2754	<b>103.7 C</b>	3054
Alliant Reloder 22	Remington	CCI 250	89.9	2721	<b>99.9</b>	3047
IMR 7828	Remington	CCI 250	94.0	2748	<b>104.4 C</b>	3041
Alliant Power Pro 4000-MR	Remington	CCI 250	88.0	2781	<b>97.9</b>	3038
Alliant Reloder 23	Remington	CCI 250	91.4	2789	<b>101.3 C</b>	3034
Alliant Reloder 16	Remington	CCI 250	85.1	2751	<b>94.6</b>	3024
Accurate 4350	Remington	CCI 250	87.3	2721	<b>96.6</b>	3018
Alliant Reloder 17	Remington	CCI 250	82.4	2704	<b>91.6</b>	3008
Ramshot Hunter	Remington	CCI 250	87.5	2770	<b>97.8</b>	3002
Hodgdon H4350	Remington	CCI 250	85.1	2723	<b>94.6</b>	2989
Hodgdon H4831	Remington	CCI 250	91.7	2717	<b>101.7</b>	2985

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*