



## 378 Weatherby Magnum

<b>.375"</b>	<b>375 Grand Slam® SP/CANN</b>
<b>Weight (grains)</b>	285
<b>Ballistic Coefficient</b>	0.354
<b>Sectional Density</b>	0.290
<b>COAL Tested</b>	3.640"
<b>Speer Part No.</b>	2473

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
<b>Alliant Power Pro 4000-MR</b>	Weatherby (Norma)	CCI 250	108.0	3024	<b>112.4</b>	3128
<b>Hodgdon SUPERFORMANCE</b>	Weatherby (Norma)	CCI 250	112.5	3025	<b>116.5</b>	3128
<b>Alliant Reloder 23</b>	Weatherby (Norma)	CCI 250	108.0	2971	<b>113.0 C</b>	3101
<b>IMR 7828</b>	Weatherby	CCI 250	109.0	2812	<b>115.0</b>	2996
<b>IMR 4831</b>	Weatherby	CCI 250	103.0	2823	<b>109.0</b>	2989
<b>Alliant Reloder 25</b>	Weatherby	CCI 250	113.0	2848	<b>117.0 C</b>	2974
<b>Alliant Reloder 22</b>	Weatherby	CCI 250	106.0	2788	<b>112.0</b>	2971
<b>Alliant Reloder 19</b>	Weatherby	CCI 250	105.0	2796	<b>111.0</b>	2967
<b>IMR 4350</b>	Weatherby	CCI 250	99.0	2862	<b>105.0</b>	2948
<b>Accurate 4350</b>	Weatherby	CCI 250	100.0	2732	<b>108.0</b>	2918
<b>Hodgdon H4350</b>	Weatherby	CCI 250	97.0	2746	<b>103.0</b>	2912
<b>IMR 4955</b>	Weatherby (Norma)	CCI 250	100.0	2763	<b>103.6</b>	2879

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*