



## 44 Remington Magnum (Rifle)

.429"	44 DCHP	44 DCSP
Weight (grains)	240	240
Ballistic Coefficient	0.175	0.175
Sectional Density	0.186	0.186
COAL Tested	1.590"	1.595"
Speer Part No.	4455	4456

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon H110	Winchester	CCI 350	22.0	1675	<b>24.0</b>	1796
Hodgdon Lil' Gun	Winchester	CCI 350	21.0	1664	<b>23.0</b>	1787
Winchester 296	Winchester	CCI 350	22.0	1624	<b>24.0</b>	1739
Alliant 2400	Winchester	CCI 300	19.0	1514	<b>21.0</b>	1701
Vihtavuori N110	Winchester	CCI 300	18.0	1540	<b>20.0</b>	1647
IMR 4227	Winchester	CCI 350	21.4	1495	<b>23.4</b>	1628
Accurate No. 9	Winchester	CCI 300	18.0	1474	<b>20.0</b>	1623
Ramshot Enforcer	Winchester	CCI 350	18.5	1477	<b>20.5</b>	1614
Accurate No. 7	Winchester	CCI 300	15.5	1354	<b>17.5</b>	1532
H. Universal	Winchester	CCI 300	8.8	1091	<b>9.6</b>	1216

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*