



45-70 Government (Strong Actions)

.458"	45
	SPFN Hot-Cor®
Weight (grains)	350
Ballistic Coefficient	0.218
Sectional Density	0.238
COAL Tested	2.710"
Speer Part No.	2478

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Accurate 2015	Winchester	CCI 200	54.0	1926	60.0	2146
Vihtavuori N133	Winchester	CCI 200	56.0	1943	60.0 C	2117
IMR 4198	Winchester	CCI 200	46.5	1941	51.5	2061
Hodgdon H4895	Winchester	CCI 200	57.0	1774	63.0 C	2030
IMR 3031	Winchester	CCI 200	55.0	1823	61.0 C	2027
Hodgdon H322	Winchester	CCI 200	54.0	1879	60.0	2027
IMR 4895	Winchester	CCI 200	55.0	1839	61.0 C	2027
Alliant Reloder 10X	Winchester	CCI 200	46.0	1893	50.0	1993
IMR 4064	Winchester	CCI 200	56.0	1675	62.0 C	1917
IMR 4320	Winchester	CCI 200	58.0	1751	62.0 C	1888
IMR SR 4759 (reduced load)	Winchester	CCI 200	28.0	1346	32.0	1503

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load