



450 Marlin

| | |
|------------------------------|-------------|
| .458" | 45 |
| Weight (grains) | SPFN |
| Ballistic Coefficient | 400 |
| Sectional Density | 0.259 |
| COAL Tested | 0.272 |
| Speer Part No. | 2.552" |
| | 2479 |

| Propellant | Case | Primer | START CHARGE | | MAXIMUM CHARGE | |
|---------------------------|---------|---------|-----------------|----------------------------|-----------------|----------------------------|
| | | | Weight (grains) | Muzzle Velocity (feet/sec) | Weight (grains) | Muzzle Velocity (feet/sec) |
| Alliant AR-Comp | Hornady | CCI 200 | 52.0 | 1977 | 56.0 C | 2133 |
| Alliant Power Pro 1200-R | Hornady | CCI 200 | 50.0 | 1990 | 53.6 | 2130 |
| Hodgdon BENCHMARK | Hornady | CCI 200 | 52.0 | 1949 | 56.0 C | 2106 |
| Alliant Power Pro Varmint | Hornady | CCI 200 | 56.0 | 1947 | 59.0 C | 2057 |
| Hodgdon H322 | Hornady | CCI 200 | 47.5 | 1781 | 51.5 C | 1990 |
| Accurate 2230 | Hornady | CCI 250 | 47.0 | 1852 | 51.0 | 1978 |
| Vihtavuori N133 | Hornady | CCI 200 | 46.0 | 1765 | 50.0 C | 1964 |
| Alliant Reloder 7 | Hornady | CCI 200 | 43.0 | 1819 | 47.0 | 1963 |
| Hodgdon Varget | Hornady | CCI 200 | 53.0 | 1821 | 57.0 C | 1962 |
| IMR 4198 | Hornady | CCI 200 | 39.0 | 1780 | 43.0 | 1930 |
| Accurate 2015 | Hornady | CCI 200 | 47.0 | 1735 | 51.0 C | 1914 |
| Vihtavuori N120 | Hornady | CCI 200 | 40.0 | 1766 | 44.0 | 1905 |
| Winchester 748 | Hornady | CCI 250 | 54.0 | 1745 | 56.0 C | 1817 |
| IMR 3031 | Hornady | CCI 200 | 48.0C | 1661 | 50.0 C | 1783 |
| Hodgdon H4227 | Hornady | CCI 200 | 32.0 | 1563 | 36.0 | 1724 |

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load