



6.5 Grendel

.264"	6.5mm
	GD
Weight (grains)	120
Ballistic Coefficient	0.457
Sectional Density	0.246
COAL Tested	2.260"
Speer Part No.	264120GDB

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pro 2000-MR	Federal	Federal 205 AR	28.4	2390	31.4	2620
Alliant Power Pro Varmint	Federal	Federal 205 AR	24.5	2264	27.3	2483
Winchester 748	Federal	Federal 205 AR	25.7	2268	28.6	2481
Alliant Reloder 15	Federal	Federal 205 AR	25.1	2246	27.9 C	2469
Ramshot TAC	Federal	Federal 205 AR	25.1	2267	27.9	2469
Hodgdon Varget	Federal	Federal 205 AR	24.1	2202	26.8	2420
Alliant AR-Comp	Federal	Federal 205 AR	22.7	2228	25.3	2418
IMR 4895	Federal	Federal 205 AR	24.0	2191	26.6	2413
Accurate 4064	Federal	Federal 205 AR	24.8	2215	27.4 C	2408
IMR 8208 XBR	Federal	Federal 205 AR	22.9	2210	25.4	2405
Vihtavuori N135	Federal	Federal 205 AR	21.7	2162	24.1	2326

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load