



6mm Creedmoor

.243"	6mm
	Spitzer BTSP
Weight (grains)	100
Ballistic Coefficient	0.446
Sectional Density	0.242
COAL Tested	2.700"
Speer Part No.	1220

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 26	Hornady	CCI 200	43.8	2953	48.7 C	3293
Alliant Power Pro 4000-MR	Hornady	CCI 200	40.9	2918	45.4	3221
Alliant Reloder 23	Hornady	CCI 200	42.6	2917	47.5 C	3219
Alliant Reloder 22	Hornady	CCI 200	41.1	2962	45.7	3212
Alliant Reloder 19	Hornady	CCI 200	41.6	2922	46.7	3206
IMR 7828	Hornady	CCI 200	42.3	2877	47.1 C	3199
Alliant Reloder 17	Hornady	CCI 200	38.3	2906	42.5	3192
Alliant Reloder 16	Hornady	CCI 200	38.7	2919	43.5	3191
Hodgdon 4350	Hornady	CCI 200	38.1	2880	42.3	3119
Accurate 4350	Hornady	CCI 200	38.2	2913	42.2	3111
IMR 7977	Hornady	CCI 200	44.3	2790	49.1 C	3101
IMR 4831	Hornady	CCI 200	39.7	2806	44.1	3082

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load