



## 6mm Remington

<b>.243"</b>	<b>6mm</b>
	<b>Spitzer SP Hot-</b>
	<b>Cor®</b>
<b>Weight (grains)</b>	90
<b>Ballistic Coefficient</b>	0.365
<b>Sectional Density</b>	0.218
<b>COAL Tested</b>	2.775"
<b>Speer Part No.</b>	1217

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 26	Federal	Federal 210	45.2	2961	<b>50.0 C</b>	3334
Alliant Power Pro 4000-MR	Federal	Federal 210	42.4	2973	<b>46.9</b>	3281
Alliant Reloder 16	Federal	Federal 210	40.8	2968	<b>45.2 C</b>	3281
Alliant Reloder 17	Federal	Federal 210	40.7	2924	<b>45.2</b>	3261
Alliant Reloder 22	Remington	CCI 200	47.0	3063	<b>51.0 C</b>	3258
Alliant Reloder 19	Remington	CCI 200	46.0	2976	<b>50.0</b>	3256
Accurate 4350	Remington	CCI 200	44.0	2852	<b>48.0 C</b>	3205
IMR 4451	Federal	Federal 210	40.4	2889	<b>44.9</b>	3191
Hodgdon H4350	Remington	CCI 200	43.0	2821	<b>47.0</b>	3170
Accurate 3100	Remington	CCI 200	45.0	2870	<b>49.0 C</b>	3154
Alliant Reloder 23	Federal	Federal 210	44.1	2981	<b>46.5 C</b>	3146
IMR 4350	Remington	CCI 200	42.0	2858	<b>46.0</b>	3107
Winchester 760	Remington	CCI 250	41.0	2811	<b>45.0</b>	3055
IMR 4831	Remington	CCI 200	43.0	2755	<b>47.0</b>	3026
Hodgdon H414	Remington	CCI 250	40.0	2759	<b>44.0</b>	2999
IMR 4064	Remington	CCI 200	35.0	2685	<b>39.0</b>	2982
Accurate 2700	Remington	CCI 250	39.0	2706	<b>43.0</b>	2974
IMR 4895	Remington	CCI 200	34.0	2711	<b>38.0</b>	2967
Vihtavuori N140	Remington	CCI 200	35.0	2675	<b>39.0</b>	2908
IMR 4198 (reduced load)	Remington	CCI 200	17.0	1770	<b>19.0</b>	1987

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*