



## 7mm Mauser (7x57mm)

.284"	7mm Spitzer BTSP	7mm Spitzer SP Hot-Cor®	7mm Grand Slam® SP/CANN
Weight (grains)	145	145	145
Ballistic Coefficient	0.472	0.416	0.353
Sectional Density	0.257	0.257	0.257
COAL Tested	2.800"	2.800"	2.970"
Speer Part No.	1628	1629	1632

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 19	Remington	CCI 200	48.0	2571	52.0 C	2831
Hodgdon H4350	Remington	CCI 200	46.0	2547	50.0 C	2820
Alliant Power Pro 4000-MR	Federal	Federal 210	46.2	2610	50.2 C	2807
Alliant Reloder 16	Federal	Federal 210	43.7	2620	47.3 C	2799
Accurate 4350	Remington	CCI 200	47.0	2506	51.0 C	2792
Hodgdon H414	Remington	CCI 250	44.0	2527	48.0 C	2783
IMR 4831	Remington	CCI 200	47.0	2538	51.0 C	2780
Winchester 760	Remington	CCI 250	44.0	2507	48.0 C	2778
IMR 4350	Remington	CCI 200	45.0	2494	49.0 C	2761
Alliant Reloder 17	Federal	Federal 210	42.3	2559	46.1 C	2761
Alliant Power Pro 2000-MR	Federal	Federal 210	40.9	2538	44.4	2734
Alliant Reloder 22	Remington	CCI 200	47.0	2466	51.0 C	2716
IMR 4064	Remington	CCI 200	39.0	2421	43.0	2711
Vihtavuori N160	Remington	CCI 200	44.0	2449	48.0 C	2697
IMR 4451	Federal	Federal 210	42.4	2474	46.1 C	2652
Alliant Reloder 15	Remington	CCI 200	38.0	2345	42.0	2627
IMR 4895	Remington	CCI 200	36.0	2357	40.0	2593
IMR SR 4759 (reduced load)	Remington	CCI 200	18.0	1514	22.0	1847

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load