



7mm Remington Magnum

.284"	7mm Spitzer SP Hot- Cor®	7mm Spitzer BTSP
Weight (grains)	130	130
Ballistic Coefficient	0.368	0.424
Sectional Density	0.230	0.230
COAL Tested	3.170"	3.285"
Speer Part No.	1623	1624

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 22	Remington	CCI 250	66.0	3118	70.0	3314
Alliant Reloder 26	Federal	Federal 215	65.3	2995	71.3	3304
Alliant Reloder 23	Federal	Federal 215	63.2	3021	69.2	3274
Alliant Power Pro 4000-MR	Federal	Federal 215	61.1	3007	67.1	3271
Alliant Reloder 19	Remington	CCI 250	65.0	3057	69.0	3270
Alliant Reloder 25	Federal	Federal 215	68.0	2960	75.2	3269
IMR 4831	Remington	CCI 250	61.0	3044	65.0	3243
IMR 7828	Federal	Federal 215	62.7	2990	68.7	3235
IMR 4350	Remington	CCI 250	59.0	3040	63.0	3234
Vihtavuori N165	Remington	CCI 250	68.0	3017	72.0	3231
Accurate 4350	Remington	CCI 250	60.0	3027	64.0	3227
Winchester 760	Remington	CCI 250	58.0	2989	62.0	3211
Alliant Reloder 17	Federal	Federal 215	54.8	2963	60.2	3196
Hodgdon H4350	Remington	CCI 250	60.0	3004	64.0	3189
Alliant Reloder 16	Federal	Federal 215	55.3	2959	60.9	3184
Hodgdon H414	Remington	CCI 250	58.0	2960	62.0	3164
Hodgdon H4831SC	Remington	CCI 250	62.0	3001	66.0	3141
Ramshot Hunter	Federal	Federal 215	56.2	2915	62.2	3133
Hodgdon H380	Remington	CCI 250	55.0	2841	59.0	3052
Alliant Reloder 15	Remington	CCI 250	51.0	2814	55.0	3049
IMR 4895	Remington	CCI 250	46.0	2737	50.0	2964
IMR SR 4759 (reduced load)	Remington	CCI 250	22.0	1768	26.0	2084

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load