



7mm Remington Short Action Ultra Magnum

.284"	7mm Spitzer BTSP	7mm Spitzer SP Hot-Cor®	7mm Grand Slam® SP/CANN
Weight (grains)	160	160	160
Ballistic Coefficient	0.519	0.504	0.389
Sectional Density	0.283	0.283	0.283
COAL Tested	2.800"	2.800"	2.785"
Speer Part No.	1634	1635	1638

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 25	Remington	CCI 200	62.0	2836	66.0 C	3024
IMR 7828	Remington	CCI 200	59.0	2794	63.0	2990
Alliant Reloder 22	Remington	CCI 200	57.0	2783	61.0	2930
IMR 4350	Remington	CCI 200	53.0	2731	57.0	2922
IMR 4831	Remington	CCI 200	54.0	2706	58.0	2913
Alliant Reloder 19	Remington	CCI 200	56.0	2774	60.0	2913
Accurate 3100	Remington	CCI 200	57.0	2730	61.0	2908
Hodgdon H4831SC	Remington	CCI 200	57.0	2717	61.0	2900

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load