



7mm Remington Ultra Magnum

.284"	7mm Spitzer BTSP	7mm Spitzer SP Hot-Cor®	7mm Grand Slam® SP/CANN
Weight (grains)	145	145	145
Ballistic Coefficient	0.472	0.416	0.353
Sectional Density	0.257	0.257	0.257
COAL Tested	3.600"	3.600"	3.550"
Speer Part No.	1628	1629	1632

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Vihtavuori N560	Remington	Federal 215	89.0	3280	93.0	3422
Accurate 8700	Remington	Federal 215	102.0	3068	106.0	3305
Hodgdon US 869	Remington	Federal 215	103.0	3165	107.0	3305
Hodgdon Retumbo	Remington	Federal 215	92.0	3095	96.0	3261
IMR 7828	Remington	Federal 215	85.0	3150	89.0	3259
Alliant Reloder 25	Remington	Federal 215	88.0	3089	92.0	3251
Alliant Reloder 22	Remington	Federal 215	84.0	3101	88.0	3250
Ramshot Magnum	Remington	Federal 215	89.0	3107	93.0	3236
Alliant Reloder 19	Remington	Federal 215	81.0	3058	85.0	3200

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load