



7mm Shooting Times Westerner

.284"	7mm Grand Slam® SP
Weight (grains)	175
Ballistic Coefficient	0.436
Sectional Density	0.310
COAL Tested	3.600"
Speer Part No.	1643

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Accurate 8700	Remington	CCI 250	85.0	2948	87.0	3009
Alliant Reloder 33	Federal	Federal 215	75.8	2704	83.9	2965
Alliant Reloder 50	Federal	Federal 215	76.3	2740	84.2	2957
Accurate 3100	Remington	CCI 250	71.0	2868	73.0	2951
Alliant Reloder 26	Federal	Federal 215	67.5	2664	74.8	2950
Alliant Reloder 25	Remington	CCI 250	72.0	2881	74.0	2947
IMR 7828	Remington	CCI 250	71.0	2874	73.0	2929
IMR 7977	Federal	Federal 215	69.7	2687	77.1	2915
Hodgdon Retumbo	Federal	Federal 215	69.3	2630	76.8	2912
Hodgdon H1000	Remington	CCI 250	73.0	2800	77.0	2909
IMR 4831	Remington	CCI 250	67.0	2830	69.0	2906
Alliant Reloder 23	Federal	Federal 215	64.9	2659	71.8	2893
Alliant Reloder 22	Remington	CCI 250	66.0	2746	70.0	2879

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load