



8mm Mauser (8x57mm)

.323"	8mm Spitzer SP Hot- Cor®
Weight (grains)	150
Ballistic Coefficient	0.343
Sectional Density	0.205
COAL Tested	2.890"
Speer Part No.	2277

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
IMR 4064	Remington	CCI 200	47.0	2695	51.0	2915
Hodgdon H335	Remington	CCI 250	46.0	2513	50.0	2771
IMR 3031	Remington	CCI 200	45.0	2488	49.0	2757
Alliant Reloder 15	Remington	CCI 200	47.0	2439	51.0	2726
Hodgdon H322	Remington	CCI 200	44.0	2433	48.0	2699
Vihtavuori N140	Remington	CCI 200	46.0	2436	50.0	2695
IMR 4895	Remington	CCI 200	44.0	2428	48.0	2675
IMR 4350	Remington	CCI 200	51.0	2458	55.0	2660
Accurate 2700	Remington	CCI 250	46.0	2358	50.0	2580
Hodgdon BL-C(2)	Remington	CCI 250	40.0	2324	44.0	2544
Accurate 4350	Remington	CCI 200	52.0	2317	56.0 C	2507
Hodgdon H414	Remington	CCI 250	51.0	2281	55.0	2506
IMR 4198(R)	Remington	CCI 200	24.0	1809	26.0	1955

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load