



8mm Mauser (8x57mm)

.323"	8mm
	Spitzer SP Hot-
	Cor®
Weight (grains)	200
Ballistic Coefficient	0.440
Sectional Density	0.274
COAL Tested	3.200"
Speer Part No.	2285

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon H380	Remington	CCI 250	48.0	2242	52.0	2469
IMR 4064	Remington	CCI 200	42.0	2196	46.0	2434
IMR 4350	Remington	CCI 200	49.0	2208	53.0 C	2432
IMR 4831	Remington	CCI 200	50.0	2213	54.0	2395
Winchester 760	Remington	CCI 250	48.0	2171	52.0	2392
Accurate 2700	Remington	CCI 250	44.0	2110	48.0 C	2324
Hodgdon H335	Remington	CCI 250	38.0	2066	42.0	2322
Alliant Reloder 15	Remington	CCI 200	40.0	2051	44.0	2267
Vihtavuori N140	Remington	CCI 200	39.0	2040	43.0	2242
Accurate 4350	Remington	CCI 200	46.0	2022	50.0 C	2149

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load